



# System Characterization Results for the QuickBird Sensor

Kara Holekamp, Kenton Ross, and Slawomir Blonski

Science Systems and Applications, Inc.  
John C. Stennis Space Center, MS 39529

Civil Commercial Imagery Evaluation Workshop  
Fairfax, VA, USA  
March 22, 2006



# Outline

---


- Overview
- Geopositional Characterization
  - Methodology
  - Results
- Spatial Characterization
  - Methodology
  - Results
- Radiometric Characterization
  - Methodology
  - Results
- Summary



# Overview

---

- QuickBird is a high-spatial-resolution multispectral sensor owned and operated by DigitalGlobe, Inc.
  - 60-cm resolution panchromatic
  - 2.4-m resolution multispectral
  - 4 multispectral bands: blue, green, red, and near-infrared
- NASA purchased QuickBird data through the Scientific Data Purchase project
- Data acquired over characterization sites every year for the past 5 years
- NASA team performed independent geopositional, spatial, and radiometric characterizations of purchased data
- Characterization results presented for the past 4 years



# Geopositional Characterization



# Geopositional Overview

## Products

### Standard (2A) Imagery Products (PAN & Multispectral)

“Standard Imagery products are radiometrically corrected, sensor corrected, geometrically corrected, and mapped to a cartographic projection...Geometric corrections remove spacecraft orbit position and attitude uncertainty, Earth rotation and curvature, and panoramic distortion.”

### • Coarse DEM Applied (default)

“Standard Imagery has a coarse DEM applied to it, which is used to normalize for topographic relief with respect to the reference ellipsoid.”

### • Ortho Ready

“Ortho Ready Standard Imagery has no topographic corrections, making it suitable for orthorectification. Ortho Ready Standard Imagery is projected to a constant base elevation, which is calculated on the average terrain elevation per order polygon.”

## Recent Acquisitions

- 27 OCT 2005 (Standard - Ortho Ready)
- 7 FEB 2006 (Standard - Coarse DEM)
- 23 MAR 2006 (Standard - Coarse DEM)

## Accuracies

“Standard Imagery products have an average absolute geolocation accuracy of 23-meter CE90%, excluding any topographic displacement and off-nadir viewing angle. Ground location is derived from refined satellite attitude and ephemeris information without requiring the use of Ground Control Points (GCPs).”

### REFERENCE:


DigitalGlobe, 2006. *QuickBird Imagery Products - Product Guide*.

Revision 4.7.2, October 18, p. 19

<http://www.digitalglobe.com/downloads/QuickBird%20Imagery%20Products%20-%20Product%20Guide.pdf> (accessed February 27, 2007).

# Note on Coarse DEM vs. Ortho Ready

Stennis Space Center



- In previous JACIE analyses, NASA geopositional analysis of QuickBird imagery has used the Standard Product with coarse DEM terrain corrections applied.
- In the most recent analysis, one available acquisition was the “Ortho Ready” version of the Standard Product, which has no terrain correction.
- Given the relatively flat terrain of the SSC geopositional target range (less than 8 m elevation difference across all targets spread over ~25 square miles) and higher sensor elevation angles, performance of the two products should be comparable.




# Geodetic Targets

Stennis Space Center



Fall 2005 QuickBird Mosaic with 45 Primary SSC Targets Overlaid



SSC Primary Targets:  
2.44 m in diameter, distributed  
across the Fee Area



- SSC primary targets are real-time kinematic GPS-located by the SSC survey team to absolute horizontal accuracies in the 3–6 cm range
- In addition to the primary targets, SSC maintains well over 100 secondary targets (predominantly painted manhole covers), but these targets were not used in the QuickBird characterizations



# Image Coordinates

Stennis Space Center



Step 1

## Locating Image Coordinates:

- Step to next target point
- Zoom to point using reference coordinates
- Add image coordinates to test point shapefile

**Cursor Location/Value of Point 2I**



Step 2



Step 3

Includes material © DigitalGlobe, Inc.

**RELEASED - Printed documents may be obsolete; validate prior to use.**  
National Aeronautics and Space Administration



# Geopositional Figures of Merit



- **Horizontal Bias** – an estimate of the constant error; it is the magnitude of the vector sum of the average error in the X and the Y
- **Circular Standard Error** – an estimate of the zero-mean circular equivalent error; valid even for elliptical error distributions with minimum to maximum error ratios as low as 0.6
- **RMSE** – Root mean square error (horizontal bias and zero-mean error not decoupled); *relationship to circular error statistics has a non-linear dependency on horizontal bias – not used for this analysis*
- **CE<sub>90</sub>** – The radial error that 90% of all errors in a circular distribution will not exceed; equivalent to the Circular Map Accuracy Standard
- **CE<sub>95</sub>** – The radial error that 95% of all errors in a circular distribution will not exceed; equivalent to Accuracy<sub>r</sub> (from National Standard for Spatial Data Accuracy)

# Vector Plots (1)




27 OCT 2005


CE<sub>90</sub>: 8.75 m

CE<sub>95</sub>: 8.90 m

Circular Standard Error: 0.87 m



- Similar direction and magnitude of all residuals indicates that the dominant error component is horizontal bias
- Noticeable and somewhat uniform change in direction of residuals from top to bottom indicates higher order systematic error components (a secondary effect)



# Vector Plots (2)

Stennis Space Center

**7 FEB 2006**

**CE<sub>90</sub>: 8.17 m**

**CE<sub>95</sub>: 8.38 m**

**Circular Standard Error: 0.64 m**


**23 MAR 2006**

**CE<sub>90</sub>: 15.54 m**


**CE<sub>95</sub>: 15.85 m**

**Circular Standard Error: 1.03 m**

Geometric Assessment Vector Plot  
QuickBird PAN Standard, 7 FEB 2006




Geometric Assessment Vector Plot  
QuickBird PAN Standard, 23 MAR 2006



# Scatterplot

QuickBird Scatterplot



# Geopositional Summary

Stennis Space Center



Acquisition Date	Elevation Angle (deg.)	Horizontal Bias (m)	Circular Std. Error (m)	Empirical CE <sub>90</sub> (m)	Empirical CE <sub>95</sub> (m)
23 AUG 2003	76.8°	11.24	1.33	12.67	12.76
15 SEP 2003	83.3°	16.53	0.71	17.40	17.62
21 OCT 2003	81.3°	12.20	1.09	13.63	13.72
10 JAN 2004	89.2°	15.41	0.54	16.27	16.39
23 JAN 2004	73.0°	11.58	1.11	13.36	13.49
28 JAN 2004	74.6°	18.37	0.53	18.98	19.21
21 JUL 2004	85.9°	18.47	0.31	18.75	18.84
30 AUG 2004	83.2°	25.76	0.66	26.66	26.99
5 OCT 2004	76.1°	24.50	1.01	25.62	25.93
17 JAN 2005	81.1°	34.60	0.36	34.87	34.95
12 MAR 2005	78.0°	14.39	0.34	14.99	15.16
22 JUN 2005	72.5°	15.31	0.97	16.71	17.31
6 SEP 2005	48.6°	23.84	0.61	24.73	24.85
18 OCT 2005	73.2°	12.28	1.12	13.60	13.80
27 OCT 2005	76.1°	7.95	0.87	8.75	8.90
7 FEB 2006	84.0°	6.99	0.64	8.17	8.38
23 MAR 2006	63.3°	14.03	1.03	15.54	15.85


- Blue acquisitions were characterized by South Dakota State University
- Red Acquisitions were characterized by NASA Stennis Space Center

- In recent acquisitions (**bold**), the mean CE<sub>90</sub> of QuickBird panchromatic *Standard* images was 10.8 m (95% confidence interval (CI) from 4.9 m to 16.7 m)
- Results are apparently better than previous analysis (mean CE<sub>90</sub> of 19.2 m with CI from 14.5 m to 23.8 m)
- Given only three recent acquisitions, beneficial product change is not **conclusive**



# Spatial Characterization





# Edge Response Measurements

Stennis Space Center

QuickBird panchromatic image acquired on January 10, 2004

GSD = 60 cm


Edge target tarps oriented for testing in the Easting direction

Edge target formed from two high-contrast tarps:  
nominally 3.5% and 52% reflectance,  
20 m x ~21 m each



Includes material © DigitalGlobe™

**RELEASED - Printed documents may be obsolete; validate prior to use.**  
National Aeronautics and Space Administration




zoom 2×

Image area  
selected for  
edge response  
analysis

A set of shifted  
edge response lines  
ready for analysis


04jan10163033-p2as-0000000098196\_01\_p001\_TARPS.tif






# Edge Response Analysis

- The nonlinear least-squares optimization with superposition of  $N$  sigmoidal functions is conducted seven times for  $N = 3, 5, 7, 9, 11, 13$ , and  $15$
- The value of  $N$  that provides the best fit is selected to generate final results
- Selection of the analyzed area and the optimization are repeated several times to estimate uncertainty of the results based on standard deviation




Modeled edge response



# Relative Edge Response




*Spatial resolution is characterized by a difference of normalized edge response values at points distanced from the edge by -0.5 and 0.5 GSD*



The graph shows a normalized edge response as a function of distance from the edge. The dots indicate edge response points used for calculations of the difference.

RER (Relative Edge Response) is a geometric mean of the normalized edge response differences in two mutually perpendicular directions (e.g., Easting and Northing).



RER values are in the range between 0 (impossibly bad) and 1 (excellent).




# Latest Example of QuickBird RER

Stennis Space Center

06mar15170252-p2as-005547583020\_01\_p001.tif






# 4-Year Stability of Spatial Resolution

Stennis Space Center


*For QuickBird panchromatic images processed with the cubic convolution resampling kernel, RER is approximately equal to 0.5*





# Radiometric Characterization





# Radiometric Vicarious Calibration

- Reflectance-based approach
- Ground truth collected near-coincident with a satellite overpass
  - Characterize targets: reflectance, BRDF (Bidirectional Reflectance Distribution Function)
  - Characterize atmosphere: transmission, aerosol, water vapor
- Use MODTRAN radiative transport code with ground truth data to predict at-sensor radiance
- Compare predicted at-sensor radiance to actual radiance acquired by sensor

# Ground Truth Collection and Processing






Stennis Space Center



Target



Atmosphere



RELEASED - Printed documents may be obsolete; validate prior to use.  
National Aeronautics and Space Administration

Transmission

Diffuse-to-Global Ratio

System Characterization

# Ground Truth Collection and Processing (cont)





Stennis Space Center



Target




Laboratory Calibration  
and Environmental  
Testing of Field  
Equipment



RELEASED - Printed documents may be obsolete; validate prior to use.  
National Aeronautics and Space Administration

Atmosphere




RELEASED - Printed documents may be obsolete; validate prior to use.  
National Aeronautics and Space Administration

BRDF Corrected Reflectance

Spectralon Panel Radiance






# NASA Stennis Space Center, MS

Stennis Space Center


QuickBird Imagery  
February 7, 2006  
True-Color Pan-Sharpned



RELEASED - Printed documents may be obsolete; validate prior to use.  
Includes material © DigitalGlobe™

# Wiggins, MS, East

Stennis Space Center



Residue  
Field

Rye Grass  
Field

Gravel Pit  
Sand Site

Golf Course with  
Radiometric Tarps

QuickBird Imagery  
January 7, 2006  
True-Color Pan-Sharpned





# Wiggins, MS, West

Stennis Space Center



Radiometric  
Tarps



Gravel Pit  
Sand Site







QuickBird Imagery  
January 25, 2006  
True-Color Pan-Sharpned



# Data Acquisitions




Site/Date	Overpass Time (UTC)	Satellite Elevation	Satellite Azimuth	Sun	
				Elevation	Azimuth
Wiggins East 1/7/06	17:05	67.8 deg	301.9 deg	35.3 deg	163.7 deg
Wiggins West 1/25/06	17:05	68.8 deg	304.0 deg	38.1 deg	160.7 deg
Stennis 2/7/06	17:01	83.9 deg	356.4 deg	41.0 deg	157.0 deg
Wiggins East 3/15/06	17:02	76.9 deg	321.3 deg	54.2 deg	152.7 deg




# QuickBird Blue Band Calibration Summary



## Blue Band Calibration Summary







# QuickBird Green Band Calibration Summary

Stennis Space Center

## Green Band Calibration Summary






# QuickBird Red Band Calibration

Stennis Space Center

## Summary


### Red Band Calibration Summary



# QuickBird NIR Band Calibration Summary



## NIR Band Calibration Summary



# 2006 QuickBird Radiometric Assessment



## Average Spectral Radiance Calibration Coefficients





Bandwidth FWHM ( $\mu\text{m}$ )	NASA Estimate ( $\text{W}/\text{m}^2 \text{ sr } \mu\text{m DN}$ )	QuickBird Provided ( $\text{W}/\text{m}^2 \text{ sr } \mu\text{m DN}$ )	% Difference
1    0.445 - 0.510	$0.255 \pm 0.013$	0.236	7.5%
2    0.500 - 0.595	$0.156 \pm 0.008$	0.145	7.1%
3    0.620 - 0.690	$0.187 \pm 0.011$	0.179	4.3%
4    0.755 - 0.875	$0.132 \pm 0.006$	0.135	-2.3%

Percent difference is calculated by  $(1 - \text{QuickBird}/\text{NASA Mean})$




# Radiometric Temporal Results

Stennis Space Center



# System Characterization Summary



- Geopositional Characterization
  - The mean  $CE_{90}$  of QuickBird panchromatic Standard images was 10.8 m, with the 95% CI from 4.9 m to 16.7 m
  - Results appeared improved over the previous analyses, which had mean  $CE_{90}$  of 19.2 m with CI from 14.5 m to 23.8 m
- Spatial Characterization
  - The QuickBird panchromatic cubic convolution resampled imagery RER is approximately 0.5
  - The spatial resolution of QuickBird has been temporally stable
- Radiometric Characterization
  - The QuickBird calibration coefficients continue to agree reasonably well with the NASA estimates (within 8%)
  - The QuickBird temporal radiometric calibration has been extremely stable (differences in estimates from 2.5% to 4.5%)

# Contributors

---



## **NASA Stennis Space Center**

Troy Frisbie

Thomas Stanley

## **Science Systems and Applications, Inc.**

Brennan Grant

Mary Pagnutti

Ruby Stubbs

Kelly Knowlton

Robert E. Ryan

Steve Tate

Roxzana Moore

## **Computer Sciences Corporation**

Ronald Vaughan

